



SECTION THRU BACKBOARD AT GOAL MOUNTING HOLES

BACKBOARD SHOWN FROM BACKSIDE

- 01214-000 RECTANGULAR ACRYLIC BACKBOARD WITH STEEL FRAME
- 01214-000 — 01214-000 RECTANGULAR ACRYLIC BACKBOARD WITH STEEL FRAME
- See B-324-72 — 00324-672 BACKBOARD PADDING KIT - BLACK (EACH)
- See B-1217 — 01217-400 BACKBOARD MOUNTING KIT WITH HARDWARE (USE TO ATTACH BACKBOARD TO EXISTING FAN BACKBOARD SUPPORT STRUCTURES)
- See B-1219 — 01219-200 BACKBOARD MOUNTING KIT WITH HARDWARE (USE TO ATTACH UPPER DIAGONAL BRACING ON EXISTING No. 164, 166, 184 AND 186 STYLE OUTDOOR BACKSTOPS)

REVISION	DATE	porter [®] No.
△		
△		CUSTOMER No.
△		
© COPYRIGHT 1995 PORTER ATHLETIC EQUIPMENT CO. ALL RIGHTS RESERVED		DATE
		10-6-1995

01214-000
3'-6" x 6'-0" RECTANGULAR ACRYLIC BACKBOARD with STEEL FRAME

THIS PRINT IS THE PROPERTY OF PORTER ATHLETIC EQUIPMENT COMPANY AND MAY NOT BE REPRODUCED WITHOUT WRITTEN PERMISSION

porter[®]
 WORLD LEADER
 IN QUALITY SPORTS EQUIPMENT
 2500 S. 25th AVENUE
 BROADVIEW, ILLINOIS 60155
 www.porter-ath.com

DRAWING BY	RJM
CHECKED BY	EAS
PAGE No.	B-1214

SPECIFICATIONS

PORTER No. 01214-000 - 3'-6" x 6' **RECTANGULAR ACRYLIC BACKBOARD**

Backboard shall be official size, 3'-6" x 6'-0".

Backboard frame shall be of a welded, unitized construction fabricated from heavy-wall rectangular steel tubing. Unitized frame shall include two (2) vertical struts located on 2'-11" centers with mounting holes for attachment to support structures. Goal mounting area shall be reinforced by horizontal and vertical support tubing to minimize undue loading on the acrylic section during slam-dunks, etc. Entire unitized frame structure shall be powder coated in a durable neutral gray, weather-resistant finish before final assembly.

Acrylic shall be provided in 1/2" thick high grade material with superior hazing, ultra-violet exposure, scratch resistance, stiffness, and impact strength. Official white border and target area shall be silk screened on the backside of the acrylic to prevent markings from wearing. Acrylic section shall be secured to the unitized rear frame by means of an attractive, L-shaped aluminum extrusion perimeter frame which is secured with truss-head type rivets. Goal mounting holes (4) to be on a 5" x 5" hole pattern.

Backboard recommended for either indoor or outdoor usage.

PORTER No. 01217-400 BACKBOARD MOUNTING KIT

Specify when backboard is to be installed to existing support structures on 2'-11" mounting centers.

PORTER No. 01219-200 BACKBOARD MOUNTING KIT

Specify when mounting backboard to existing No. 164, 166, 184, or 186 outdoor backstops.

OPTIONAL ITEMS TO SPECIFY

- See Page No. B-324-72 for specifications on Porter No. 00324-672 Backboard Padding Kit.
- See Page No. B-1217 for specifications on Porter No. 01217-400 Backboard Mounting Kit.
- See Page No. B-1219 for specifications on Porter No. 01219-200 Backboard Adapter Kit.