



- 00216-000 THE MEDALLION™ RECTANGULAR FIBERGLASS BACKBOARD
- See B-326 — 00326-XXX PADDING KIT - BOLT-ON (EACH) - INDOOR USE
SEE PAGE No. B-326 FOR AVAILABLE COLORS
- See B-227 — 00227-000 PADDING KIT - TAPE-ON - GRAY (PAIR) - INDOOR USE
- See B-324-72 — 00324-672 PADDING KIT - BOLT-ON - BLACK (EACH) - OUTDOOR USE

PATENT No. 5,207,419

REVISION	DATE	Porter No.
△		
△		
△		

DATE
4-1-2005

00216-000
3'-6" x 6'-0" MEDALLION™
RECTANGULAR FIBERGLASS BACKBOARD

THIS PRINT IS THE PROPERTY OF PORTER ATHLETIC EQUIPMENT COMPANY
AND MAY NOT BE REPRODUCED WITHOUT WRITTEN PERMISSION

PORTER
WORLD LEADER
IN QUALITY SPORTS EQUIPMENT
2500 S. 25th AVENUE
BROADVIEW, ILLINOIS 60155
www.porter-ath.com

DRAWING BY RJM
CHECKED BY EAS
PAGE No. B-216

SPECIFICATIONS

PORTER No. 00216-000 MEDALLION™ **MOLDED FIBERGLASS BACKBOARD** **(PATENT No. 5,207,419)**

Backboard size shall be 42" x 72" x 2" (1.07m x 1.83m x 5cm), with official orange perimeter and target area markings. Backboard is molded from high tensile strength fiberglass Sheet Molded Compound (SMC) with heavy perimeter flange and structural rib patterns to provide maximum rigidity and superior rebound qualities. Laminated backboards with a wood or honeycomb type core will not be accepted as equal. Goal mounting area shall be structurally reinforced with a heavy 3/16" x 6" x 1' 10-1/2" (.5cm x 15.2cm x 57.2cm) galvanized steel plate secured to backside of backboard.

Backboard shall also be provided with two additional counter-bored holes behind goal mount area for independently mounting backboard to a Center-Strut® type support system when removal of goal is desirable. Direct mount hardware (two, 3/8" x 3" Lg. plated carriage bolts) is provided with backboard. Goal mounting centers shall be slotted to accommodate goals with a 5" (12.7cm) horizontal x 4 1/2" to 5" (11.4cm to 12.7cm) vertical spacing. Backside of backboard shall be provided with eight (8) 3/8"-16 x 1" deep threaded stainless steel mounting inserts which are located in place at standard 2'-11" (88.9cm) horizontal x 1'-8" (50.8cm) vertical spacing during the molding process. Backboard attachment to support structure utilizing through bolt type installation shall not be considered equal.

Backboard protected by a limited 10-year warranty against structural defects when installed on Porter Center-Strut® support systems.

OPTIONAL ITEMS TO SPECIFY

- See Page No. B-326 for specifications on Porter No. 00326-XXX Backboard Padding Kits (indoor use).
- See Page No. B-227 for specifications on Porter No. 00227-000 Backboard Padding Kit (indoor use).
- See Page No. B-324-72 for specifications on Porter No. 00324-672 Backboard Padding Kit (outdoor use).