

SPECIFICATIONS

PORTER No. 475100 ALUMINUM SOCCER GOALS LESS BACKSTAYS AND NET IN-GROUND / SLEEVE-TYPE (ONE PAIR)

Soccer goals shall meet all NFHS and NCAA requirements for championship soccer tournaments. The bottom edge of the horizontal crossbar shall be located 8'-0" above the playing field, with the uprights positioned with a 24'-0" inside dimension. Goals shall be furnished in three sections (crossbar and two uprights) for ease of assembly or dismantling for seasonal use.

Crossbar and uprights are constructed of a 4" square lightweight high-tensile (6063-T6) aluminum extrusion finished in a durable white powder-coated finish. All aluminum extrusion sections shall be designed with an internal continuous channel configuration, and furnished with special molded, high-tensile nylon no-tie net attachment clips for ease of installing or removing the nets. Uprights shall be secured to the crossbar with formed steel corner brackets. Formed corner brackets shall be finished in a durable white powder-coated finish.

Uprights shall extend 2'-0" into concrete footings. (Specify optional No. 00444000 ground sleeves when removal of goals is required.)

OPTIONAL ITEMS TO SPECIFY

- See Page No. R-444 for specifications on Porter No. 00444000 Outdoor Ground Sleeve (Each) when removal of goals is required.
- See Page No. R-469 for specifications on Porter No. 00469204 Upright Padding (Set of Two, for one goal).
- See Page No. R-291-2 for specifications on Porter No. 291200 Standard Backstays (Set of Four).
- See Page No. R-292-2 for specifications on Porter No. 292200 European Backstays (Set of Four).
- See Page No. R-422 for specifications on Porter No. 00422040 Backpost Net Supports (Set of Four).
- See Page No. R-490 for Soccer Goal Net selection information.
(Specify No. 00490824, 00491824 or 00492824, depending on type of backstay.)